

CDP0700

METHODS, ARTICLES AND APPARATUS FOR ADVERTISING BASED
ON AN ATTRIBUTE OF A COMPUTER NETWORK RESOURCE

Technical Field .

5

The present invention relates to methods, articles and apparatus for advertising.

Background of the Invention

10

Many Internet portals provide a search engine with which a user may initiate an Internet search. The search engine returns a list of Web pages based upon a search expression received from the user.

15

Some search engines display a similarity value for each Web page in the list. Each similarity value numerically indicates a degree of correlation or relevance between its corresponding Web page and the search expression.

20

Oftentimes, the Web pages in the list are sorted based on the similarity values. By sorting the Web pages in this manner, the list presents highly-relevant Web pages before lesser-relevant Web pages.

25

Some Internet portals provide directories of Web pages. These directories provide a tree-like structure of categories and subcategories within which Web pages are classified.

30

Pub. p. 1 DoubleClick, Inc. provides various Internet advertising solutions. These solutions include providing advertising for an Internet portal at

Sp. pointed

www.AltaVista.com. Advertising on a search results page may be targeted based upon a keyword in a search expression submitted to www.AltaVista.com.

5

Brief Description of the Drawings

The present invention is pointed out with particularity in the appended claims. However, other features are described in the following detailed description in conjunction with the accompanying drawings in which:

10

FIG. 1 is a block diagram of an embodiment of a system for providing advertising; and

15

FIG. 2 is a block diagram of another embodiment of a system for providing advertising.

Detailed Description of Preferred Embodiments

Improved methods, articles and apparatus for advertising are disclosed herein. Advertising for a Web resource is targeted and/or accounted for based upon an advertiser-usable variable specific to the Web resource. The advertiser-usable variable is provided by a referring Web resource having a hyperlink to the Web resource. The advertiser-usable variable may comprise either a similarity value between the Web resource and a search expression, a similarity value between the Web resource and the referring Web resource, or a tree-defined attribute of the Web resource, for example.

25

30

After the hyperlink is user-selected from the referring Web resource, an advertisement is selected from a plurality of advertisements based on the advertiser-usable variable. The advertisement is
5 provided to the client node to display with the Web resource.

In this way, different referring Web resources providing a hyperlink to the Web resource may provide different values of the advertiser-usable variable
10 specific to the Web resource. For example, one referring Web resource may use one tree to define a tree-defined attribute of the Web resource, and another referring Web resource may use a different tree to define a tree-defined attribute of the Web resource.
15 Thus, different ones of the advertisements may be displayed with the Web resource depending on which referring Web resource's hyperlink was user-selected.

The present disclosure also contemplates a single referring Web resource which provides varying values of
20 the tree-defined attribute of the Web resource. For example, the value of the tree-defined attribute of the Web resource may be dependent upon a search expression which identified the Web resource. Thus, different ones of the advertisements may be displayed with the
25 Web resource for different searches which identified the Web resource.

FIG. 1 is a block diagram of an embodiment of a system for providing advertising. A client node 10 generates and sends a request message 14 to a content
30 node 12 via a computer network (not specifically

illustrated) in accordance with a communication protocol. Examples of the client node 10 include, but are not limited to, a client computer system and a personal digital assistant. Examples of the content
5 node 12 include, but are not limited to, a server computer system. Examples of the computer network include, but are not limited to, an internet, an intranet and an extranet. Examples of the protocol include, but are not limited to, HTTP (hypertext
10 transfer protocol) and WAP (wireless application protocol).

The request message 14 requests a resource, such as a Web resource, from the content node 12. In response to the request message 14, the content node 12
15 generates and sends one or more response messages to the client node 10 via the computer network. The one or more response messages provides a Web resource 16 to the client node 10 via the computer network.

The Web resource 16 comprises a plurality of user-selectable hyperlinks. For purposes of illustration and example, the user-selectable hyperlinks include a first user-selectable hyperlink 20 to a first Web resource available from a first content node 22, a second user-selectable hyperlink 24 to a second Web resource available from a second content node 26, and a
25 third user-selectable hyperlink 30 to a third Web resource available from a third content node 32. Each of the content nodes 22, 26 and 32 may be embodied by a respective one of three different server computer
30 systems, for example. The content nodes 22, 26 and 32

may have any physical location relative to the content node 12. For example, each of the content nodes 22, 26 and 32 may be either proximate to or distantly located from the content node 12. Similarly, each of the
5 content nodes 22, 26 and 32 may have any physical location relative to others of the content nodes 22, 26 and 32. For example, each of the content nodes 22, 26 and 32 may be located in geographically diverse locations. Although illustrated with three user-
10 selectable hyperlinks, the Web resource 16 may comprise any number of user-selectable hyperlinks to a plurality of Web resources in general.

To identify the plurality of Web resources, the content node 12 may perform a search based on a search expression received from the client node 10. The
15 search expression may be user-entered using an input device such as a keyboard, a touch screen, a touch pad or a voice input device associated with the client node 10. The search expression may contain one or more
20 words in the form of either a Boolean search expression or a natural language search expression, for example. The search expression may include information from a plurality of user-enterable fields to limit the scope of the search. The search expression may include an
25 image or encoded audio.

The search performed via the content node 12 yields search results comprising the plurality of Web resources, the plurality of Web resources being a subset of a larger set of Web resources. The content
30 node 12 may use scripting code to provide, within the

Web resource 16, the user-selectable hyperlinks
associated with the search-identified Web resources.

The Web resource 16 further comprises a plurality
of advertiser-usable variables within at least one
5 script 34. Each of the at least one script 34 may
include script code either directly within the Web
resource 16, or within a separate file called by
computer program code within the Web resource 16.
Examples of programming languages for the at least one
10 script 34 include, but are not limited to, JavaScript
and VBScript.

For purposes of illustration and example, the
advertiser-usable variables include one or more
advertiser-usable variables 36 specific to the first
15 Web resource, one or more advertiser-usable variables
40 specific to the second Web resource, and one or more
advertiser-usable variables 42 specific to the third
Web resource. Each of the one or more advertiser-
usable variables 36, 40 and 42 has a corresponding
20 value usable by an advertisement server node 44 to
select advertising content to display with its
corresponding Web resource. The advertisement server
node 44 may be embodied by a server computer system,
for example. The advertisement server node 44 may have
25 any physical location relative to the content nodes 12,
22, 26 and 32.

In the case of the Web resource 16 providing
search results, the one or more advertiser-usable
variables 36 may indicate a similarity value between
30 the search expression and the first Web resource, the

one or more advertiser-usable variables 40 may indicate a similarity value between the search expression and the second Web resource, and the one or more advertiser-usable variables 42 may indicate a

5 similarity value between the search expression and the third Web resource. Each similarity value indicates a degree of similarity, relevance or correlation between the search expression and its corresponding Web resource. Preferably, each similarity value numerically

10 indicates the degree of similarity, relevance or correlation. For example, each similarity value may comprise an integer from 0 to 100. Alternatively, each similarity value may qualitatively indicate the degree of similarity, relevance or correlation. For example,

15 each similarity value may indicate either high similarity, moderate similarity or low similarity. Regardless of whether the similarity value is quantitative or qualitative, it is preferred that the similarity value be capable of indicating a plurality

20 of different levels of similarity. More preferably, the similarity value is capable of indicating at least three different levels of similarity.

Alternatively, for both search and non-search applications, the content node 12 may determine a tree

25 which relates the plurality of Web resources. In this case, each of the one or more advertiser-usable variables 36, 40 and 42 may include a value defined by the tree. The content node 12 may use various computer-readable data structures to represent the tree

in a computer-readable form using a computer-readable medium.

Before proceeding, a review of trees and graph-related terminology is provided. A graph is definable
5 by a set of nodes and a set of edges joining or associating different pairs of distinct nodes. The edges in the graph may be either directed or undirected.

Alternative terminology may be used to describe
10 the graph. Examples of synonyms of "node" include, but are not limited to, "vertex" and "state". Examples of synonyms of "edge" include, but are not limited to, "arc" and "link". Therefore, the herein-disclosed methods, articles, apparatus, and examples should not
15 be limited by the selected terminology used to describe the graph.

A first node is said to be adjacent to a second node if there is an edge from the first node to the second node. A path is definable by a sequence of
20 nodes wherein each consecutive pair of nodes in the sequence is adjacent.

A tree is a graph having a unique path from a designated node, called a root node, to each of its other nodes. If the tree is undirected, then any of
25 its nodes can be designated to be the root node. An undirected tree can be made into a directed tree by directing all edges away from the designated root node.

Each node in a directed tree, except for the root node, is a child node of a unique parent node from
30 which an edge is directed thereto. Nodes having the

same parent node are called siblings. Nodes of a directed tree with no children are called leaf nodes. Nodes having at least one child are called internal nodes. The level number of a node is defined as the
5 number of edges in the path between the node and the root node. The height of the tree is the largest level number of any node.

If each internal node of a rooted tree has m children, the tree is called an m -ary tree. If $m=1$,
10 the tree is unary. If $m=2$, the tree is binary. If $m=3$, the tree is ternary.

Each of the Web resources is represented by a corresponding node of the tree. Relationships between Web resources are represented by edges in the tree.
15 Examples of edge-represented relationships between items include, but are not limited to, a degree of similarity, a hyperlink, an associative link, a state of being an element of, a state of being contained in, a state of being associated with, a state of reporting to, a state of being in a category, a state of depending from, and a state of being a reply to.

The tree may be unary to define a browsing sequence for the Web resources. In other cases, the tree is non-unary, i.e. the tree has at least one
25 internal node with two or more child nodes. In some cases for a non-unary tree, the tree may have more leaf nodes than a number of child nodes emanating from its root node. Regardless of whether the tree is unary or non-unary, it is preferred that the tree has a height

of at least two. In some cases, the tree may have a height of three or greater.

For Web resources comprising computer-readable messages, an edge in the tree may indicate that one
5 message is a reply to another message. Thus, a reply message is a child of its parent message, and two reply messages to the same parent message are siblings. Each base message, i.e. each message that begins a new thread, may have an associated edge to a root node in
10 the tree. If a search is performed, the root node may represent a Web resource associated with the search expression. Regardless of whether a search is performed, the root node may represent a Web resource
associated with a discussion group of which the
15 messages are elements.

In some embodiments, the content node 12 provides the tree by determining an optimum path tree based upon
a first plurality of similarity values between the search expression and the Web resources, and a second
20 plurality of similarity values between pairs of the Web resources. The optimum path tree indicates a
respective optimum path between the search expression and each of the plurality of Web resources.

5
*
↓
The optimum path between the search expression and
25 a Web resource has an optimum function value of similarity values between the search expression and the Web resource. Examples of the function whose optimum value dictates the optimum path include, but are not limited to, a sum of similarity values between the
30 search expression and the Web resource, and a product

of similarity values between the search expression and the Web resource. To determine an optimum product of similarity values, an additive optimum path algorithm may be performed on a logarithm of the similarity values. For example, if the similarity values are numerical values between 0% and 100%, then an additive minimum path algorithm may be performed on a negative logarithm of the non-zero similarity values, e.g. $-\log(\text{similarity value})$, to determine a maximum product of similarity values.

As is known in the art of network algorithms, examples of algorithms to compute the shortest paths include, but are not limited to, Dijkstra's algorithm and Floyd's algorithm. Those having ordinary skill can review shortest path algorithms on pp. 123-127 of A. Tucker, Applied Combinatorics, Second Edition, John Wiley & Sons, 1984, which is hereby incorporated by reference into this disclosure.

Alternatively, the content node 12 may provide the tree by determining a spanning tree based upon the first plurality of similarity values and the second plurality of similarity values. Examples of the spanning tree include, but are not limited to, an optimum spanning tree such as a minimum spanning tree, and a search tree.

The optimum spanning tree has an optimum function value of similarity values. Examples of the function whose optimum value dictates the optimum spanning tree include, but are not limited to, a sum of similarity values, and a product of similarity values. To

determine an optimum product of similarity values, an additive optimum spanning tree algorithm may be performed on a logarithm of the similarity values.

As is known in the art of network algorithms, examples of algorithms to compute a minimum spanning tree include, but are not limited to, Kruskal's algorithm and Prim's algorithm. Those having ordinary skill can review minimum spanning trees on pp. 127-131 of A. Tucker, Applied Combinatorics, Second Edition, John Wiley & Sons, 1984, which is hereby incorporated by reference into this disclosure.

Examples of the search tree include, but are not limited to, a depth-first search spanning tree, a breadth-first search spanning tree, or a best-first search spanning tree. Those having ordinary skill can review search trees on pp. 80-122 of A. Tucker, Applied Combinatorics, Second Edition, John Wiley & Sons, 1984, which is hereby incorporated by reference into this disclosure.

Each of the one or more advertiser-usable variables 36, 40 and 42 may indicate a level number of its corresponding Web resource within the tree. For example, the one or more advertiser-usable variables 36 may indicate a level number of the first Web resource within the tree, the one or more advertiser-usable variables 40 may indicate a level number of the second Web resource within the tree, and the one or more advertiser-usable variables 42 may indicate a level number of the third Web resource within the tree. Each

level number may be indicated numerically by an integer, e.g. 1, 2, 3, etc.

Alternatively, each of the one or more advertiser-usable variables 36, 40 and 42 may indicate whether its
5 corresponding Web resource is an internal resource of the tree or a leaf resource of the tree. For example, the one or more advertiser-usable variables 36 may indicate that the first Web resource is an internal resource of the tree, and the one or more advertiser-usable variables 40 may indicate that the second Web
10 resource is an internal resource of the tree. As another example, the one or more advertiser-usable variables 36 may indicate that the first Web resource is an internal resource of the tree, and the one or more advertiser-usable variables 40 may indicate that the second Web resource is a leaf resource of the tree.
15 As a further example, the one or more advertiser-usable variables 36 may indicate that the first Web resource is a leaf resource of the tree, and the one or more advertiser-usable variables 40 may indicate that the
20 second Web resource is a leaf resource of the tree.

As another alternative, each of the one or more advertiser-usable variables 36, 40 and 42 may be based on the ancestry of its corresponding Web resource
25 within the tree. The one or more advertiser-usable variables 36 may be based on which of the Web resources having a predetermined level number is an ancestor of the first Web resource in the tree, the one or more advertiser-usable variables 40 may be based on which of
30 the Web resources having the predetermined level number

is an ancestor of the second Web resource in the tree, and the one or more advertiser-usable variables 42 may be based on which of the Web resources having the predetermined level number is an ancestor of the third Web resource in the tree. Of particular interest is where the predetermined level number is one.

Preferably, each of the one or more advertiser-usable variables 36, 40 and 42 also identifies its corresponding Web resource. For example, the one or more advertiser-usable variables 36 may include a computer address of the first Web resource, the one or more advertiser-usable variables 40 may include a computer address of the second Web resource, and the one or more advertiser-usable variables 42 may include a computer address of the third Web resource. Examples of each computer address include, but are not limited to, a uniform resource locator (URL), a uniform resource name (URN), a uniform resource identifier (URI) and an internet protocol (IP) address.

Alternatively, the one or more advertiser-usable variables 36 may include a first non-address identifier of the first Web resource, the one or more advertiser-usable variables 40 may include a second non-address identifier of the second Web resource, and the one or more advertiser-usable variables 42 may include a third non-address identifier of the third Web resource.

In some embodiments, the at least one script includes two advertiser-usable variables for each hyperlink: one identifying the Web resource corresponding to the hyperlink, and another indicating

either the similarity value or the tree-defined value.
Alternatively, a single advertiser-usable variable may
both identify the Web resource and indicate either the
similarity value or the tree-defined value.

5 The Web resource 16 includes computer program code
to generate a request message, such as an advertisement
request message 46 or another request message. Based
on the computer program code, the client node 10
generates and sends the advertisement request message
10 46 to the advertisement server node 44 via the computer
network. The advertiser request message 46 requests a
resource, such as a Web resource, from the
advertisement server node 44. In response to the
advertisement request message 46, the advertisement
15 server node 44 generates and sends one or more response
messages to the client node 10 via the computer
network. The one or more response messages may provide
an advertisement resource 50 to the client node 10 via
the computer network. Examples of the advertisement
20 resource 50 include, but are not limited to, visible
advertisements such as a banner advertisement, a button
advertisement, a badge advertisement, a text link
advertisement, a rich media advertisement and a pop-up
window advertisement, and audible advertisements. The
25 advertisement resource 50 is displayed with the Web
resource 16 by the client node 10. It is noted that
providing the advertisement resource 50 is optional.

(read cookies)
30 Regardless of whether the advertisement resource
50 is provided, the one or more response messages
facilitate reading the plurality of advertiser-usable

1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2

unreadably
cookie
PA

20

After the at least one cookie 52 has been provided
to the client node 10, any of the user-selectable
hyperlinks 20, 24 and 30 may be user-selected from the
Web resource 16 using the client node 10. For purposes
of illustration and example, consider the user
selecting the first user-selectable hyperlink 20 from
the Web resource 16 using the client node 10. In

response thereto, the client node 10 generates and sends a request message to the content node 22 via the computer network. The request message requests a resource, such as a Web resource, from the content node 5 22. In response to the request message, the content node 22 generates and sends one or more response messages to the client node 10 via the computer network. The one or more response messages provides a Web resource 54 to the client node 10 via the computer 10 network.

The Web resource 54 includes computer program code to generate an advertisement request message 56. Based on the computer program code, the client node 10 generates and sends the advertisement request message 15 56 to the advertisement server node 44 via the computer network. Based on the advertisement request message 56, the one or more advertiser-usable variables 36' associated with the Web resource 54 are retrieved from the at least one cookie 52. Either the advertisement request message 56 or a variable within a script of the 20 Web resource 54 may identify the Web resource 54 to facilitate the one or more advertiser-usable variables 36' being distinguished from the other variables 40' and 42' using the herein-disclosed Web resource 25 identifiers in the at least one cookie 52.

Preferably, the one or more advertiser-usable variables 36' are retrieved by or otherwise communicated to the advertisement server node 44. In this case, the advertisement server node 44 selects an 30 advertisement from a plurality of advertisements based

on the one or more advertiser-usable variables 36'.
Alternatively, the one or more advertiser-usable
variables 36' are retrieved by the client node 10,
which selects an advertisement from a plurality of
5 advertisements based thereon.

The advertisement may be selected using one or
more targeting criteria for the one or more advertiser-
usable variables 36'. For example, some of the
advertisements may have a targeting criterion to enable
10 advertising only with Web resources having a similarity
value within a prespecified range. An advertisement
may have a respective numerical range of acceptable
similarity values (e.g. from 85 to 100), or a
respective qualitative range of acceptable similarity
15 values (e.g. high similarity). In these cases, higher
billing rates may be charged for advertising with Web
resources having higher similarity values (all other
factors being equal).

As another example, some of the advertisements may
20 have a targeting criterion to enable advertising only
with Web resources having a level number within a
prespecified range. An advertisement may have a
respective numerical range of acceptable level numbers
(e.g. only a level number of 1, only a level number of
25 2, level numbers from 3 to 4, or level numbers of 3 and
greater). In some cases, higher billing rates may be
charged for advertising with Web resources having lower
level numbers (all other factors being equal).
Optionally, the tree defining the level number is

unary, such as a browsing sequence for the Web resources.

As a further example, some of the advertisements may have a targeting criterion to enable advertising only with Web resources which are internal resources of a tree, and others may have a targeting criterion to enable advertising only with Web resources which are leaf resources of the tree. In some cases, higher billing rates may be charged for advertising with internal resources than for leaf resources (all other factors being equal).

As a still further example, some of the advertisements may have a targeting criterion to enable advertising only with Web resources having an ancestor resource, at a predetermined level number in the tree, which meets at least one criterion. In this case, for example, higher billing rates may be charged for advertising with Web resources having a higher-similarity-value ancestor resource at the predetermined level number (all other factors being equal).

In the case of the advertisement server node 44 selecting the advertisement, the advertisement server node 44 generates and sends one or more response messages to provide an advertisement resource 60 to the client node 10 via the computer network. Examples of the advertisement resource 60 include, but are not limited to, visible advertisements such as a banner advertisement, a button advertisement and a pop-up window advertisement, and audible advertisements. The

advertisement resource 60 is displayed with the Web resource 54 by the client node 10.

Optionally, the advertisement server node 44 may update a data structure associated with the advertisement resource 60 based on the one or more advertiser-usable variables 36'. The data structure may include a count which is incremented based on the one or more advertiser-usable variables 36'. The count may indicate a number of impressions of the advertisement resource 60 for a particular range of an advertiser-usable variable. Alternatively, the count may indicate a number of click-throughs of the advertisement resource 60 for a particular range of an advertiser-usable variable. Each particular range may comprise a single value or a plurality of values.

The data structure is used to generate an advertising report associated with the advertisement resource 60. The advertising report may include a breakdown of a number of impressions and/or click-throughs for each particular range^{of} an advertiser-usable variable.

Similar acts are performed in response to user-selection of the second user-selectable hyperlink 24 from the Web resource 16 using the client node 10. In particular, (a) a request message is generated and sent to the content node 26 via the computer network, (b) the content node 26 provides to the client node 10 via the computer network a second Web resource including computer program code to generate an associated advertisement request message, (c) the client node

generates and sends the advertisement request message to the advertisement server node 44, (d) the advertising request message associated with the second Web resource is received by the advertisement server
5 node 44, (e) the one or more advertiser-usable variables 40' is retrieved from the at least one cookie 52, (f) an advertisement from the plurality of advertisements is selected based on the one or more advertiser-usable variables 40', and (g) and the
10 advertisement is provided to display with the second Web resource by the client node 10. Similar acts are performed in response to user-selection of the third user-selectable hyperlink 30 from the Web resource 16 using the client node 10.

15 FIG. 2 is a block diagram of another embodiment of a system for providing advertising. The embodiment of FIG. 2 differs from the embodiment of FIG. 1 in that the advertisement server node 44, upon receiving the advertisement request message 46, reads the plurality
20 of advertiser-usable variables 36, 40 and 42, and stores corresponding advertiser-usable variables 36", 40" and 42" in a database 70 before any of the user-selectable hyperlinks 20, 24 and 30 have been user-selected from the Web resource 16 using the client node
25 10.

Further, the advertisement server node 44 optionally provides at least one cookie 72 for the client node 10 before any of the user-selectable hyperlinks 20, 24 and 30 have been user-selected from
30 the Web resource 16 using the client node 10. The at

least one cookie 72 stores an identification code 74. The database 70 also stores an identification code 74" corresponding to the identification code 74. The identification codes 74 and 74" are used to associate the advertiser-usable variables 36", 40" and 42" in the database 70 to the client node 10. The database 70 may use various computer-readable data structures to store the identification code 74" and the advertiser-usable variables 36", 40" and 42" in a computer-readable form using a computer-readable medium.

PA
In general, the at least one cookie 72 may be either readable or unreadable by the content nodes 12, 22, 26 and 32. Typically, however, the at least one cookie 72 is unreadable by the content nodes 12, 22, 26 and 32.

Alternatively, the identification code 74 may not be included in at least one cookie 72 and/or may not be provided by the advertisement server node 44. In these cases, the identification code 74 may be pre-stored in the client node 10 to uniquely identify the client node 10. In this case, the advertisement server node 44 may read the identification code 74 from the client node 10, and thereafter store the corresponding identification code 74" in the database 70 and associate the corresponding identification code 74" with the advertiser-usable variables 36", 40" and 42".

After the advertiser-usable variables 36", 40" and 42" have been stored in the database 70, any of the user-selectable hyperlinks 20, 24 and 30 may be user-selected from the Web resource 16 using the client node

10. For purposes of illustration and example, consider the user selecting the first user-selectable hyperlink 20 from the Web resource 16 using the client node 10. In response thereto, the client node 10 generates and
5 sends a request message to the content node 22 via the computer network. The request message requests a resource, such as a Web resource, from the content node 22. In response to the request message, the content node 22 generates and sends one or more response
10 messages to the client node 10 via the computer network. The one or more response messages provides a Web resource 54 to the client node 10 via the computer network.

The Web resource 54 includes computer program code
15 to generate the advertisement request message 56. Based on the computer program code, the client node 10 generates and sends the advertisement request message 56 to the advertisement server node 44 via the computer network. Based on the advertisement request message
20 56, the advertisement server node 44 uses the identification code 74 from the client node to retrieve one or more advertiser-usable variables 36" associated with the Web resource 54 from the database 70. Either the advertisement request message 56 or a variable
25 within a script of the Web resource 54 may identify the Web resource 54 to facilitate the one or more advertiser-usable variables 36" being distinguished from the other variables 40" and 42" using the herein-disclosed Web resource identifiers in the database 70.

The advertisement server node 44 selects an advertisement from a plurality of advertisements based on the one or more advertiser-usable variables 36". The advertisement server node 44 generates and sends
5 one or more response messages to provide the selected advertisement resource 60 to the client node 10 via the computer network. The advertisement resource 60 is displayed with the Web resource 54 by the client node 10.

10 Similar acts are performed in response to user-selection of either the second user-selectable hyperlink 24 or the third user-selectable hyperlink 30 from the Web resource 16 using the client node 10. Although not specifically illustrated, the database 70
15 typically stores identification codes and associated advertiser-usable variables for a plurality of different client nodes.

With reference to either FIG. 1 or FIG. 2, each of the client node 10, the content node 12, the content
20 node 22, the content node 26, the content node 32 and the advertisement server node 44 may comprise one or more programmed computers. Each programmed computer may provide a particular functionality implemented using hardware and/or software and/or firmware.

25 Preferably, each programmed computer includes a processor responsive to a computer memory to perform a series of specifically identified operations dictated by a computer program. In this way, the computer program can cause the computer to act in a particular
30 fashion.

Examples of the processor include, but are not limited to, a general purpose microprocessor, an application-specific integrated circuit (which may be either standard or custom), one or more discrete logic
5 elements, a digital signal processor, one or more circuits, or any combination thereof. It is noted that the processor may be embodied by either a single processing unit or a plurality of processing units.

Examples of the computer memory include, but are
10 not limited to, an electronic memory, a magnetic memory, an optical memory, and a magneto-optical memory. Examples of an electronic memory include, but are not limited to, a programmable electronic memory and a read-only, hard-wired electronic memory.
15 Examples of a magnetic memory include, but are not limited to, a magnetic disk and a magnetic tape. The magnetic disk may be embodied by a magnetic floppy diskette or a magnetic hard drive, for example. Examples of an optical memory include, but are not
20 limited to, an optical disk. The optical disk may be embodied by a compact disk or a DVD, for example. Regardless of its form, the computer memory may be either read-only, once-writable, or rewritable.

In general, the processor may be responsive to any
25 data structures, computer programs, and signals encoded on a computer-readable medium to perform an embodiment of any of the herein-disclosed methods and examples. Examples of the computer-readable medium include, but are not limited to, computer-readable storage media and
30 computer-readable communication media. Examples of

computer-readable storage media are described with reference to the computer memory. Examples of computer-readable communication media include, but are not limited to, an optical medium, an electronic
5 medium, and an electromagnetic medium.

The client node 10 may cooperate in a client-server fashion with the advertisement server node 44 and the content nodes 12, 22, 26 and 32, for example. The client node 10 communicates with the advertisement
10 server node 44 and the content nodes 12, 22, 26 and 32 in accordance with a communication protocol. Examples of the protocol include, but are not limited to, HTTP and WAP.

The client node 10 includes a display device to
15 display Web resources and selected advertisement resources. Examples of the display device include, but are not limited to, a computer monitor, a television, a liquid crystal display, a cathode ray tube, and a gas plasma display.

The client node 10 receives user-initiated
20 selections and other user input from one or more user input devices. Examples of input devices include, but are not limited to, a pointing device, a keyboard, and a voice input device. Examples of pointing devices
25 include, but are not limited to, a mouse, a touchpad, a trackball, a joystick, a pointing stick and a touchscreen.

A selection of a hyperlink is detected in response to a user-initiated event. Examples of the user-
30 initiated event include, but are not limited to, an on-

click event, a double-click event, a mouse-move event, a mouse-over event, a mouse-out event, a mouse-up event, and a key depression event. The display and the one or more user input devices facilitate user
5 interaction with the client node 10.

The client node 10 includes a transceiver to communicate with the computer network. Examples of the transceiver include, but are not limited to, a modem, a network interface, and a wireless transceiver.

10 It is noted that each of the herein-disclosed Web resources may include computer program code in a markup language such as hypertext markup language (HTML), wireless markup language (WML) or handheld device markup language (HDML). For example, some of the
15 herein-disclosed Web resources may comprise World Wide Web pages.

It will be apparent to those skilled in the art that the disclosed inventions may be modified in numerous ways and may assume many embodiments other
20 than the preferred forms specifically set out and described herein.

Accordingly, it is intended by the appended claims to cover all modifications which fall within the true spirit and scope of the present invention.

25 What is claimed is: